


XS-SERIES TOPLOADING BALANCES

FEATURES

- Vacuum-fluorescent display
- Rapid update of displayed weight (no overshooting of target weights)
- Stability indicator
- Rapid response time (2 seconds)
- Die-cast aluminum construction
- Stainless steel weighing pan
- Overload protection
- Below-pan weighing
- UL approved
- Spill cover
- DI's 5-year, no-nonsense warranty




SPECIFICATIONS

DI MODEL	DENVER INSTRUMENT CAT NO	CAPACITY	SENSITIVITY	PAN SIZE	REPEATABILITY	LINEARITY
XS-210	8529.1	210g	0.001g	4"	0.001g	±0.002g
XS-410	8530.1	410g	0.01g	5.5"	0.01g	±0.01g
XS-2100	8532.1	2100g	0.1g	5.5"	0.1g	±0.1g
XS-310D	8531.1	310/31g	0.01/0.001g	4"	0.01/0.001g	±0.01/0.002g

COMMON SPECIFICATIONS

Stabilization time	2 seconds
Net weight	7 lbs
Temperature specifications	59-104F (15-40C)
Electrical requirements	115 VAC to 12 VDC transformer included. 230 VAC to 12 VDC transformer available upon request
Dimensions (L x W x H)	10 x 8.5 x 2.5" (25 x 22 x 6 cm)

XS-SERIES TOPLOADERS



FEATURES

- Die-Cast Aluminum
- Stainless Steel Pan
- Automatic Calibration
- Solid-State Electronics
- Vacuum-Fluorescent Display
- Silicone-Sealed Key Pad
- In-Use Cover (Standard)
- Full-Range Taring
- One Button Operation
- Below-Pan Weighing
- Lock Down Device (Optional)
- External Power Supply (12V)
- Overload Protection
- Five Year Warranty
- Made in the U.S.A. (Since 1880)
- DEMO EXPRESS

BENEFITS

- Durable, Long Lastin
- Non-Corrosive
- Ensures Accurate Readings, Preset
- Fast, Reliable Response Time
- Bright, Easy to Read
- Spill Protection
- Spill Protection
- Ability to Subtract Container Weight
- Ease of Use, Simple
- Specific Gravity Capability
- Theft Protection
- Safe, Portable
- Protection Against Abuse
- Worry-Free Operation
- Over 100 Years of Experience
- No Risk Test Drive